

A Fusion of "Core" Dispensing Technologies MUSASHI's motion units

SHOTMASTER 500SX-SS
 SHOTMASTER 400SX-SS
 SHOTMASTER 300SX-SS
 SHOTmini 200SX-SS
 SHOTmini 100SX-SS

«Ultimate cost-effective performance»

Newly
Developed



CE
RoHS



- ◆ 800 mm/s, highest level of operation speed in this class.
- ◆ ±0.01 mm repetitive positioning accuracy.
- ◆ **Newly developed** Synchro Speed function. PAT.P
 The line width can be maintained at constant even when moving through a corner.
 Maximum reduction in cycle time for the highest production efficiency.

Fully enhanced operability

New type teaching pendant

- Equipped with **interactive user-friendly interface**
- **Stopwatch function**
- **Dispensing condition switching function**
- **Data transfer function between robots**
- Available in **Japanese, English, and Chinese**



Multifunctional machine

Substantial hardware configuration

- **External input/output:26/26**
- **USB port**
High-speed communication
- **"START" button, "STOP" button, "RETURN TO ORIGIN" button, "DISPENSE" button** equipped as standard
- **Z-axis brake function**

Optional

Nozzle adjuster

Automated nozzle position offset adjustment after syringe replacement.



